


MJ12832B



②MECHANICAL SPECIFICATIONS

Item	Normal Dimensions(mm)
Module Size(W×H×T)	80.6×42.8×12.9
Viewing Area(W×H)	60.0×18.0
Dot Pitch(W×H)	0.44×0.49
Dot Size(W×H)	0.40×0.45

④FEATURE

LCD Type & Colour	STN:Yellow-Green、 Blue,FSTN
View Angle	6 O'clock
Display Type	Positive Type,Negative Type
Control IC & Package	ST7920,COB
Operating Temperature	-20℃～70℃
Storage Temperature	-30℃～80℃

③PIN CONNECTIONS

Pin	Symbol	Function
1	V0	Power supply for LCD Driver
2	VR	Voltage Doubler Ouput
3	VSS	Ground for Logic(0V)
4	VDD	Power supply for Logic(+5V)
5	NC	No Connect
6	RS	H: Data;L: Instruction Code (P) / Clock (S)
7	R/W	H: Read; L: Write(P) / Data input (S)
8	E	Enable Signal (P) / Chip Select(S)
9~16	DB0~DB7	Data Bus Line
17	PSB	H:Parallel Mode; L:Serial Mode
18	/RST	Reset Signal (Active Low)
19	LED+	Backlight Power (+5V)
20	LED-	Backlight Power (0V)

⑤ELECTRICAL CHARACTERISTICS (Supply current doesn't contain backlight)

Item	Symbol	Test Condition	Typ.	Unit
Operating Voltage	Vdd	Ta=25℃	5.0	V
Supply Current	Idd	Ta=25℃ , Vdd=5.0V	2.0	mA